



Dimensions	35C12			35C15/18		
	MWB	LWB	XLWB	MWB	LWB	XLWB
A Wheelbase	3450	3750	4100	3450	3750	4100
B Overall length	5899	6509	6909	5899	6509	6909
C Front overhang	998	998	998	998	998	998
D Rear overhang	1355	1665	1715	1355	1665	1715
E Maximum cab width	1996	1996	1996	1996	1996	1996
F Front axle to back of cab	2105	2105	2105	2105	2105	2105
H Front axle to body	2160	2160	2160	2160	2160	2160
Cab gap	55	55	55	55	55	55
K Overall height (unladen)	2220	2215	2210	2220	2215	2210
L Frame height at rear	740	740	740	740	740	740
Turning circle (k to k) (m)	11.7	12.5	13.5	11.7	12.5	13.5
Turning circle (w to w) (m)	12.8	13.7	14.7	12.8	13.7	14.7

Body Dimensions						
Maximum body width	2200	2200	2200	2200	2200	2200
Option	2350	2350	2350	2350	2350	2350
Recommended max body length	3135	3745	4155	3135	3745	4155

Weights (kg)						
Kerb weights are with full fuel tank, oil, water, spare wheel, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.						
Model	35C12			35C15/18		
Wheelbase	3450	3750	4100	3450	3750	4100
GVW	3500	3500	3500	3500	3500	3500
GTW	7000	7000	7000	7000	7000	7000
Kerb weights						
Front axle	1400	1415	1435	1420	1435	1460
Rear axle	685	680	670	695	695	680
Total	2085	2095	2105	2115	2130	2140
Maximum body & payload	1415	1405	1395	1385	1370	1360
Plated weights						
Front axle	1800	1800	1800	1800	1800	1800
Rear axle	2600	2600	2600	2600	2600	2600

Engines	C12	C15	C18
Fuel	Diesel	Diesel	Diesel
Capacity (litres)	2.3	3.0	3.0
Cylinders	4 (16 valves)		
Emission Compliance	Euro 4		
Fuel System	Common rail Generation 2		
Power (hp/ kW)	116/ 85	146/ 107	176/ 130
@ rpm	3200-3900	3000-3500	3200-3500
Torque (Nm/ lbft)	270/ 199	350/ 258	400/ 295
@ rpm	1800-2800	1400-2600	1250-3000
Exhaust system	Centre emit		

Gearboxes	C12	C15	C18
Type	5S300OD	6S400OD	6S400OD
	5 speed	6 speed	6 speed
	Synchromesh		
	Overdrive		
1st gear	4.99 : 1	5.37 : 1	5.37 : 1
Top gear	0.78 : 1	0.79 : 1	0.79 : 1

Performance

Gear	1st	Top	1st	Top	1st	Top
Max. geared speed (mph)	15	89	12	84	13	89
Gradeability @ GVW (%)	40+	7	40+	9	40+	10

Rear Axle Ratios

Standard	4.18	3.91	3.6
----------	------	------	-----

Clutch	C12	C15	C18
Type	Hydraulic	Hydraulic	Hydraulic
Diameter	267	280	280

Standard Equipment

Cab (6+1)

Drivers airbag with seat belt pretensioners
 Dual passenger seat with headrests
 Fully adjustable driver's seat with headrest
 4 passenger rear seat with headrests
 Large dual storage pockets in doors
 Three point inertia reel belt on front seats and rear outer seats. Inertia lap belt for rear centre seats
 Single piece floor mat
 Exterior mirrors with integrated wide angle and direction indicators
 2 cup holders
 Underseat storage
 Bottle holder
 Glove compartment with added storage
 A4 storage compartment
 Additional in-dash storage
 Cooled compartment (with opt. air conditioning)
 Clip holder
 Rear panel with small window
 Rear door with sliding window
 Additional light in rear

Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation
 Windshield and side window defrost facility
 Fresh air ventilation when heater turned off

Dashboard incorporates

Dash-mounted gear lever
 RDS stereo radio/CD player (with Can security)
 Provision for GPS or tachograph
 Coolant temperature indicator
 Speedometer
 Rev.counter

Dashboard incorporates (cont'd)

3 DIN drawers, two of which carry CD Player and/or tachograph
 LCD Display Panel includes: odometer, trip computer with distance, time, fuel consumption etc; headlamp orientation (dip/main); clock

Security

Central locking with remote control and door locking management - anti-theft system
 Engine immobiliser
 Steering lock

Chassis

Flat topped high tensile steel c-section frame complete with pedestal body mounting brackets
 Rear underslung spare wheel and carrier
 Rear under ride guard

Construction & Finish

C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full cathodic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

Electrics

Alternator - std 14v - 110A
 Alternator - opt 14v - 140A
 Battery 12v - 110Ah
 13 pin towing electrics (.14/.15/.18 engines only)

Lighting & Signalling

Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

Suspension

Front Independent with transverse leaf spring
 Rear Semi-elliptic leaf spring
 Anti-roll Bar Front and rear
 Shock absorbers Front and rear

Brakes

Front / diameter Ventilated disc brakes / 290 mm
 Rear / diameter Ventilated disc brakes / 290 mm
 ABS + EBD Standard
 Parking brake On rear axle

Steering

Power assisted - Rack & Pinion

Wheels & Tyres

Wheels 6JK 16
 Tyres 195/65R16
 Spare Standard

Fuel Tank

70 litres on nearside with locking fuel cap

Options

AGile semi-automated 6-speed gearbox
 Dual front passenger airbag with seat belt pretensioners (in addition to std. drivers airbag)
 Dual front passenger airbag with seatbelt pretensioners (in addition to std. drivers airbag) and additional driver and passenger window airbags
 Air conditioning
 Alarm system
 Alternator- heavy duty
 Ambient air temperature gauge (option with air conditioning)
 ASR - Traction control
 Blue Tooth vivavoice system with steering wheel controls - Blue & me
 Body builder connectors
 Colour keyed bumper and trim
 Comfort dashboard - LCD panel
 additions include: dual trip function; servicing indicator; door locking function; speed alarm; fuel economy indicator; external temperature display and ice warning indicator are also shown only when climate control is specified. Automated gearbox information is also displayed when Agile gearbox is specified.
 Comfort seats - driver and passenger
 ECAS air suspension on rear axle
 ESP - Electronic Stability Programme (includes ABS - Anti-lock Brakes, EBD - Electronic Brake Force Distribution, ASR - Traction Control, MSR - Motor Torque Reduction, HBA - Hydraulic Brake Assist)
 Exhaust with CRT
 Exterior mirrors - heated and electrically adjustable
 Fuel tank with locking cap - 100 litres
 GPS satellite navigation
 Headlamp washers
 Long external mirror arm (Standard on 60C & 65C models)

Overhead windscreen storage rack and DIN drawer
 PVC trim
 Rear axle ratio options
 Full screen satellite navigation
 Tachograph - digital
 Tow bar with ball
 Towing electric socket (13 pin) (.12 engine only)
 Windows electrically operated

For a complete list of Daily options please contact your local Iveco distributor

DAILY 35C12/15/18
CREW CAB

IVECO